TECHNICAL DATA SHEET

CARBON WINDOW FILM

SHADE 03 · CARBON LINE

CARBON 03

2% VISIBLE LIGHT	**51.3%** SOLAR ENERGY REJECTED
99% UV REJECTED	**43%** IR REJECTED



PERFORMANCE DATA

Visible light transmitted (VLT)	2%
Total solar energy rejected	51.3%
UV rejected	99%
IR rejected	43%
IR rejected (0.9–1.0 µm)	46%
Visible light reflectance — interior	4.6%
Visible light reflectance — exterior	4.5%
Thickness	2.0 mil

BENEFITS

- **Maximum privacy**
  The darkest shade in the Carbon Line, for maximum privacy.
- **Solar heat control**
  Rejects 51.3% of total solar energy for a cooler cabin.
- **UV protection**
  Blocks 99% of UV rays, protecting passengers and interiors.
- **Low-reflective finish**
  Only 4.6% interior and 4.5% exterior reflectance — no mirror look.
- **Carbon film technology**
  2.0 mil carbon construction.

THE CARBON LINE

03	05	15	20
35	40	50	70

All tested materials were applied on a ¼" clear glass surface in accordance with industry standard tests. Data is for comparison purposes only. NIR: 900–1000 nm range.

DC INTERNATIONAL
7868 NW 62nd Street, Miami, FL 33166
305-431-6570 · WhatsApp
www.dcifilms.com