TECHNICAL DATA SHEET

CARBON WINDOW FILM

SHADE 35 · CARBON LINE

CARBON 35

37% VISIBLE LIGHT	**38.8%** SOLAR ENERGY REJECTED
99% UV REJECTED	**43%** IR REJECTED



PERFORMANCE DATA

Visible light transmitted (VLT)	37%
Total solar energy rejected	38.8%
UV rejected	99%
IR rejected	43%
IR rejected (0.9–1.0 µm)	46%
Visible light reflectance — interior	5.1%
Visible light reflectance — exterior	5%
Thickness	2.0 mil

BENEFITS

- **Privacy with a clear view**
  A medium shade that balances privacy and visibility.
- **Solar heat control**
  Rejects 38.8% of total solar energy for a cooler cabin.
- **UV protection**
  Blocks 99% of UV rays, protecting passengers and interiors.
- **Low-reflective finish**
  Only 5.1% interior and 5% exterior reflectance — no mirror look.
- **Carbon film technology**
  2.0 mil carbon construction.

THE CARBON LINE

03	05	15	20
35	40	50	70

All tested materials were applied on a ¼" clear glass surface in accordance with industry standard tests. Data is for comparison purposes only. NIR: 900–1000 nm range.

DC INTERNATIONAL
7868 NW 62nd Street, Miami, FL 33166
305-431-6570 · WhatsApp
www.dcifilms.com