TECHNICAL DATA SHEET

HYBRID AUTO WINDOW FILM

SHADE 20 · FUSION LINE

FUSION 20

19% VISIBLE LIGHT	**51%** SOLAR ENERGY REJECTED
99% UV REJECTED	**40%** IR REJECTED



PERFORMANCE DATA

Visible light transmitted (VLT)	19%
Total solar energy rejected	51%
UV rejected	99%
IR rejected	40%
Visible light reflectance — interior	11%
Visible light reflectance — exterior	8%
Thickness	1.5 mil

THE FUSION LINE

05 | **20** | 35 | 50 | 70

BENEFITS

- **High privacy, less glare**
  A dark shade that cuts glare and keeps the interior private.
- **Solar heat control**
  Rejects 51% of total solar energy for a cooler cabin.
- **UV protection**
  Blocks 99% of UV rays, protecting passengers and interiors.
- **Non-reflective, color-stable look**
  Only 11% interior and 8% exterior reflectance; the color stays true over time.
- **Hybrid construction**
  Color-stable dyed layer plus a metalized layer, 1.5 mil.

All tested materials were applied on a ¼" clear glass surface in accordance with industry standard tests. Data is for comparison purposes only. NIR: 900–1000 nm range.

DC INTERNATIONAL
7868 NW 62nd Street, Miami, FL 33166
305-431-6570 · WhatsApp
www.dcifilms.com