TECHNICAL DATA SHEET

HYBRID AUTO WINDOW FILM

SHADE 30 · FUSION LINE

FUSION 30



30% VISIBLE LIGHT	**50%** SOLAR ENERGY REJECTED
99% UV REJECTED	**36%** IR REJECTED

PERFORMANCE DATA

Visible light transmitted (VLT)	30%
Total solar energy rejected	50%
UV rejected	99%
IR rejected	36%
Visible light reflectance — interior	11%
Visible light reflectance — exterior	8%
Thickness	1.5 mil
Roll size	60″ × 100′
Warranty	10 years

THE FUSION LINE

05 | 15 | 20 | **30** | 35 | 50 | 70

BENEFITS

- **Privacy with good visibility**
  A medium-dark shade that keeps the interior private with a clear view out.
- **Solar heat control**
  Rejects 50% of total solar energy for a cooler cabin.
- **UV protection**
  Blocks 99% of UV rays, protecting passengers and interiors.
- **Non-reflective, color-stable look**
  Only 11% interior and 8% exterior reflectance; the color stays true over time.
- **Hybrid construction**
  Color-stable dyed layer plus a metalized layer, 1.5 mil.

All tested materials were applied on a ¼″ clear glass surface in accordance with industry standard tests. Data is for comparison purposes only. NIR: 900–1000 nm range.

DC INTERNATIONAL
7868 NW 62nd Street, Miami, FL 33166
305-431-6570 · WhatsApp
www.dcifilms.com