TECHNICAL DATA SHEET

HYBRID AUTO WINDOW FILM

SHADE 70 · FUSION LINE

FUSION 70

72% VISIBLE LIGHT	**35%** SOLAR ENERGY REJECTED
99% UV REJECTED	**65%** IR REJECTED

PERFORMANCE DATA

Visible light transmitted (VLT)	72%
Total solar energy rejected	35%
UV rejected	99%
IR rejected	65%
Visible light reflectance — interior	11%
Visible light reflectance — exterior	8%
Thickness	1.5 mil

THE FUSION LINE

05 | 20 | 35 | 50 | **70**

BENEFITS

- **Clear, natural look**
  The lightest shade in the line, with 65% IR rejection.
- **Solar heat control**
  Rejects 35% of total solar energy for a cooler cabin.
- **UV protection**
  Blocks 99% of UV rays, protecting passengers and interiors.
- **Non-reflective, color-stable look**
  Only 11% interior and 8% exterior reflectance; the color stays true over time.
- **Hybrid construction**
  Color-stable dyed layer plus a metalized layer, 1.5 mil.

All tested materials were applied on a ¼" clear glass surface in accordance with industry standard tests. Data is for comparison purposes only. NIR: 900–1000 nm range.

DC INTERNATIONAL
7868 NW 62nd Street, Miami, FL 33166
305-431-6570 · WhatsApp
www.dcifilms.com